



OMM GRAPHIC SDN BHD

NO. 7, JALAN TIAJ 2/9, TAMAN INDUSTRI ALAM JAYA, 42300 BANDAR PUNCAK ALAM,
SELANGOR, MALAYSIA
TEL: (603) 6038 6872 FAX: (603) 6038 6840

TECHNICAL INFORMATION

AP6500 FOUNTAIN SOLUTION

Characteristics:

Premium Sheetfed Fountain Solution. Desinged for wide range of water hardness. Great product for high speed machines.

Application:

All types of alcohol dampening systems on sheet-fed presses. Suitable for All types of presses.

Special Features:

- Free of VOC
- Enhance the Inks properties
- Suitable for all type of waters
- Non corrosive
- Contains anti-pilling additives
- Low foaming
- Better contrasts
- Strongly Buffered

Direction:

1. Always clean dampening system before changing fountain solution.
2. Clean Rollers with Calcium Deglazer.
3. Optimum dilution for Alcoplus is between 2%-3%.It is suggested that 2.5% is used as a suitable dilution for initial running. This may be adjusted within 2%-4%. An initial IPA setting of 8%-11% is suggested.

Packing available: -

- 1000 liter IBC Tank
- 200 liter Plastic Drum
- 25 liter Plastic Container
- 5 liter Plastic Container

